


### TANEM SERIES



- PİRİNÇ RENK AYIRICI
- ФОТОСЕПАРАТОР РИСА
- زردالیا تونلوزر
- TRIEUR DE COULEURS DE RIZ
- CLASIFICADOR DE ARROZ POR COLOR
- CLASSIFICADOR DE CORES DE LATAO

- **Remove Glass, Desiccant, Variegated Plastic.**  
Spectral confocal 3.0, the sorting accuracy is automatically adjusted.
- **Extra - Simple Operation, Easy To Use.**
- **Outstanding Output.**  
Each chute < 3.0 TPH.
- It's mainly used in the sorting of japonica rice, indica rice, glutinous rice, parboiled rice and other rice with dozens of intelligent sorting solutions.
- It features high pure rate, low loss, and stable performance.
- **Shape Sorting.**  
Long/round, large broken/medium broken/small broken.
- **Flexible Chute Setting.**  
Tertiary sorting, fourth sorting, fifth sorting, sixth sorting.
- **Highly Reliable and Smarter.**  
Standardized and modularized design.

### ■ CORE COMPETENCE



Confocal Slow Motion Camera.



Simplified Interface.



Sniper System.



New Intelligent Dust-Sucking System.



Smart Checkup.

Configuration	Performance	Key Parts	
		15-inch LED screen Nanoscale visible light ultra-clear color sensor	■
Performance	Sorting Performance	Capacity of each chute	< 3.0 TPH
		Shape sorting	■
		Full spectrum lighting system	■
		Spectrum confocal system	■
		Sniper system	■
		Service Life	Maglev ejector LED light
Impurity Removal	Glass and desiccants	●●●●●	
	Plastics	●●●●	
Air Circuit System	Intelligent feeder vacuum system	□	
	Auto cleaning + anti-rice suction	■	
Protection Device	Chute cover	□	
	Smart alarm	■	
	Intelligent Production Line	■	
Intelligence	Intelligent Production Line	Simplified interface	■
		YasarCare (App)	■
		Remote commissioning	■
		Smart checkup	■
		Smart backup	■
		Panorama quality analyzer	□

Parameters above are tested on the environment of 25°C and 2% impurities rate and may change in different conditions. ● :Function strength, ■ :Standard, □ :Selection - :No

### Technical Specifications

Model	Channels	Power	Supply voltage	Air pressure	Air consumption	Dimension (L-W-H)	Weight (KG)
R4	240	2.0	180-240V 50Hz	0.6-0.8 Mpa	<2.0m³/min	1891 × 1564 × 2020	1120
R6	360	2.7	180-240V 50Hz	0.6-0.8 Mpa	<3.0m³/min	2533 × 1564 × 2020	1400
R8	480	3.4	180-240V 50Hz	0.6-0.8 Mpa	<4.0m³/min	2991 × 1564 × 2020	1750
R10	600	4.0	180-240V 50Hz	0.6-0.8 Mpa	<5.0m³/min	3583 × 1564 × 2020	2090



Japonica Rice



Indica Rice



Whole Chalky Rice




Partial Chalky Rice



Accepts Rice



Light Yellow Rice and Sticky Rice



Transparent Rice