


TANEM MAX SERIES

-  PİRİNÇ RENK AYIRICI
-  ФОТОСЕПАРАТОР РИСА
-  زردالیا تونل زردا
-  TRIEUR DE COULEURS DE RIZ
-  CLASIFICADOR DE ARROZ POR COLOR
-  CLASSIFICADOR DE CORES DE LATAO



■ **Superior Output.**
23-39 TPH.

■ **Remove Pin-point Tips.**
Equipped with Yasar quad camera to remove pin-point tips. (optional)

■ **Higher Pure Rate.**
Equipped with infrared speed camera, more accurate.


■ It's mainly used in the sorting of japonica rice, indica rice, glutinous rice, parboiled rice and other rice with dozens of intelligent sorting solutions.

■ It's equipped with the Yasar infrared system, the sorting accuracy is automatically adjusted. It's highly efficient to remove the glass, plastic, strapping tape, stone and other foreign materials, ensuring rice quality.

■ CORE COMPETENCE



Nano HD Camera.




PID Position Control System.



Sniper System.



Intelligent Dust-Sucking System. (Optional)



Full Spectrum Lighting System.

■ **Remove Glass, Desiccant and Plastic.**
Yasar infrared system, the sorting accuracy is automatically adjusted.

■ **Shape Sorting.**
Long/round, large broken/medium broken/small broken.

■ **Highly Reliable and Smarter.**
Standardized and modularized design.

		TANEM MAX	TANEM MAX LUXURY	TANEM MAX FLAGSHIP	
Configuration	Key Parts	15-inch LED screen	■	■	
		Nanoscale visible light ultra-clear color sensor	■	■	
		Infrared speed monitor camera	■	■	
	Sorting Performance	InGaAs composite infrared imaging system	■	■	
		NIR imaging system	■	■	
		Capacity of each chute	< 3.0 TPH	< 3.0 TPH	< 3.0 TPH
		Shape sorting	■	■	
		Full spectrum lighting system	■	■	
		Spectrum confocal system	■	■	
	Service Life	Sniper system	■	■	
		Maglev ejector	●●●●●	●●●●●	●●●●●
	Impurity Removal	LED light	●●●●●	●●●●●	●●●●●
		Glass and desiccants	●●●●●	●●●●●	●●●●●
		Plastics	●●●●	●●●●	●●●●
		Same-color stones	—	●●●	●●●●
Air Circuit System	Other non-rice impurities	—	●●●	●●●●	
	Intelligent feeder vacuum system	□	□	□	
Protection Device	Auto cleaning + anti-rice suction	■	■	■	
	Chute cover	□	□	□	
Intelligence	Intelligent Production Line	Smart alarm	■	■	
		Simplified interface	■	■	
		YasarCare (App)	■	■	
		Remote commissioning	■	■	
		Smart checkup	■	■	
		Smart backup	■	■	
		Panorama quality analyzer	□	□	□

Parameters above are tested on the environment of 25°C and 2% impurities rate and may change in different conditions. ● :Function strength, ■ :Standard, □ :Selection — :No

Technical Specifications							
Model	Channels	Power	Supply voltage	Air pressure	Air consumption	Dimension (L-W-H)	Weight (KG)
TANEM MAX	RT3	5.0	180-240V 50Hz	0.6-0.8 Mpa	<6.5m³/min	4445 × 1620 × 2020	2800
TANEM MAX LUXURY	RL13	5.0	180-240V 50Hz	0.6-0.8 Mpa	<6.5m³/min	4445 × 1620 × 2020	2800
TANEM MAX FLAGSHIP	RF13	5.0	180-240V 50Hz	0.6-0.8 Mpa	<6.5m³/min	4445 × 1620 × 2020	2850



Japonica Rice



Indica Rice



Whole Chalky Rice



Partial Chalky Rice



Accepts Rice



Light Yellow Rice and Sticky Rice



Transparent Rice